

Cetol® Interior Clear

A solventborne transparent coating for interior woodwork which accentuates the natural grain and texture of all types of interior woods and provides a hard-wearing finish for doors, cabinets, furniture and many other applications. Cetol Interior Clear may be used on its own or in unison with Cetol Interior Stain. Available in a Satin finish.

Transparent coating; ensures optimum visibility of the wood texture and enhances grain definitions.

Seals and protects.

Scratch resistant.

Alcohol resistant.

Easy to clean.

Simple application.

Used as a transparent protective finish for all interior woods except floors. May be used to topcoat Cetol Interior Stain. (Refer to Sikkens Product Application Guide for details.)

Method - Long-haired, natural bristle brush, roller, or spray.

Temperature - 50°F - 95°F (10°C - 35°C).

Thinning - None, ready to use after stirring thoroughly.

Cleaning of Equipment - Mineral spirits or varsol.

Coverage - Approximately 400-500 sq. ft. per U.S. gallon (10-12 sq. m. per liter) per coat.

Drying Time - Touch dry after 2-3 hours; recoatable after 24 hours.

CHARACTERISTICS

USE

APPLICATION

Viscosity - 3.4 - 3.8 Poise at 23°C (73° F)

Density - 0.89 kg/dm³

Solids By Weight - 41%

Solids By Volume - 33%

Gloss Levels - Low Lustre, Satin, Gloss

Flow - Very Good

Durability - Very Good

V.O.C. - 3.77 lbs./gal., 538 g/L - water free

Colorless - 003

U.S. quart, U.S. gallon, U.S. 5 gallon

Shelf Life - Approximately 5 years in an unopened container.

FLASHPOINT:

Approx. 104°F (40°C) (SFCC)

WARNINGS:

DANGER! RAGS, STEEL WOOL, BRUSHES, ROLLERS AND ANY WASTE WET, SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISPOSED OR STORED. To avoid a spontaneous combustion fire, immediately after each use place rags, steel wool, brushes, rollers or waste in a sealed, water-filled metal container. Keep away from combustible materials. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency. Harmful or fatal if swallowed. Keep out of reach of children. Keep away from open flame or spark. Use only with adequate ventilation.

FIRST AID TREATMENT:

Refer to the Material Safety Data Sheet

The technical information and suggestions for use made herein are based on Akzo Nobel Coatings Inc.'s research and experience and are believed to be reliable, but such information and suggestions do not constitute a warranty.

Since Akzo Nobel Coatings has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise, the suitability of the product for their purposes. When testing, the complete system that has been chosen must be applied.



PROPERTIES




COLOR RANGE



PACKAGING



STORAGE



**HEALTH & SAFETY
DATA**



PRODUCT DISCLAIMER